


C&I ESS SOLUTION

BOS-B Pro-A3



Intelligent Control

- Peak-valley mgmt, anti-backflow,
- overload protection
- Load tracking, demand control, backup power, phase separation



Scalable

- Support up to 16 units in parallel, maximum 2.3MW/4.1MWh



Multi-Fusion

- Integrated EMS, PCS, and BMS
- Support expansion of MPPT module
- Support off-grid backup



Reliable

- Operating temp : -20°C to 55°C
- Operate up to 3000m altitude
- 1.1x overload capacity
- Balancing solutions extend battery life
- Triple auxiliary power design for stable supply



Easy Maintenance


- 5U Standard Chassis
- User Interface & Bluetooth App
- USB & Cloud Upgrades
- TCP Protocol for EMS
- Fault Signal Input Support



Safer

- LFP batteries
- Support aerosol fire extinguishing


Model	BOS-B-PDU-2-A
Operating Voltage	200~1000Vdc
Nominal Charge/Discharge Current	180A
Operating Temperature	-20~60°C
Ingress Protection	IP20
AC Input Rating	220±10%VAC/2A
Details	788.6×526×167.2(W×D×H),32kg




- ◎ Ethernet:Features not yet developed.
- ◎ PCS COM:PCS COM battery communication terminal: used to output battery information to the inverter.
- ◎ IN COM:Connection position with previous BOS-B-PDU-2 communication OUT COM .
- ◎ OUT COM:Connection position with next BOS-B-PDU-2 communication IN COM.
- ◎ Breaker:It is used to manually control the connection between the battery rack and external devices.

- ◎ COMM3:The product must be connected to the auxiliary power input AC200~240V-3A-50~60Hz when used.
- ◎ COMM1:Emergency power-off triggered the interface. RS485-Enabled.
- ◎ COMM2:Communicative connection with the first battery module; and providing 12VDC power for the first battery module.
- ◎ Bluetooth:The mobile APP connects to the data acquisition rod of the energy storage system.
- ◎ B+:Battery common positive connection position (orange).
- ◎ B-:Battery common negative connection position (black).
- Display screen:Display SOC and fault codes.
- START:A start switch of 12VDC power inside the high-voltage control box.
- ◎ HV light indicator:High-voltage hazard indicator (yellow).
- ALRM light indicator:Battery system fault alarm indicator (red).
- ◎ PCS1+:First PCS positive connection position (orange).
- ◎ PCS2+:Second PCS positive terminal connection position (orange).
- ◎ PCS1-:First PCS negative connection position (black).
- ◎ PCS2-:Second PCS negative connection position (black).
- ◎ USB:BMS upgrade port and storage expansion port.

Model	BOS-B-Pack16-A3
Nominal Capacity	314Ah
Nominal Energy	16.08kWh
Nominal Voltage	51.2Vdc
Max Charge/Discharge Current	180A
Ingress Protection	IP20
Operating Temperature(Charge)	0~55°C
Operating Temperature(Discharge)	-20~55°C
Storage Temperature	0~35°C
Details	795.9×526×274.2(W×D×H),126kg



- ◎ B+: Battery module positive pole (orange)
- ◎ B-: Battery module negative pole (black)
- ◎ Fan: Ventilation and heat dissipation.
- ◎ COMM1: Connection position of battery module communication and power supply input
- ◎ COMM2: Connection position of battery module communication and power supply output




Matching Mode	PCS or Hybrid Inverter	14-15 units for PCS on-grid applications, 15 units for PCS off-grid applications, 5-15 units for hybrid inverter systems
	PCS + MPPT	16 units (on/off-grid) for MPPT Open-Circuit Voltage $\leq 800V$; 15 units (on/off-grid) for MPPT Open-Circuit Voltage $\leq 750V$ 14 units (on-grid) for MPPT Open-Circuit Voltage $\leq 700V$

Other Parameter


Operating Temperature (°C)	Charge : 0 ~ 55						Discharge : -20 ~ 55					
Storage Temperature (°C)	0 ~ 35											
Thermal Management	Smart fan cooling											
LCD Display	SOC / Fault Code											
Status Indicator	Yellow : Battery High Voltage Power On Red : Battery System Alarm											
Communication Port	TCP / RS485 / CAN											
Communication With BMS	CAN											
Humidity	5% ~ 85%											
Altitude	≤3000m											
IP Rating of Enclosure	IP20											
Noise (dB)	TBD											
System Dimension (W × H × D, mm)	1067 × 1305 × 800			1608 × 1305 × 800				2150 × 1305× 800				
System Weight Approximate (kg)	758	884	1010	1136	1310	1436	1562	1688	1862	1988	2114	2240
Installation Location	Rack Mounted											
Recommend Depth of Discharge	90%											
Cycle Life	25±2℃, 0.5C / 0.5C, EOL70%≥6000											
Warranty Period	10 years											
Certification	CE / IEC62619 / IEC62040 / UN38.3											

Typical Application Scenarios


One PCS can support up to 16 racks of batteries in parallel



One STS module can connect to four 125kW PCS modules for parallel operation



Five STS modules can provide parallel support for twenty 125kW PCS modules, forming a 2.5MW system.




Deye Cloud

All-in-one Energy & Device Management Platform

- Unlock significant savings
- Individual Add-on for dynamic tariff
- Intelligent charging/discharging strategies
- Tailored solution to deye devices
- Real-time equipment monitoring
- Best energy scheduling solutions by Deye Copilot
- 24/7 AI Assistant support

Switch flexibly
between autonomous
and manual control



Display energy
savings and costs



Support dynamic
tariff and flat-rate

AI Assistant



Offer response suggestions
and personalized support
experience

Support over 30
languages

Analyze dynamic pricing, predict power
load and PV generation to optimize energy
dispatch and minimize electricity costs

Smarten Up Your Home Energy

Download Deye Cloud APP to join us!

Embrace a seamless, effortless energy experience that's both eco-friendly and budget-friendly with our intelligent assistant



APP & Web

Manage your
energy effortlessly



Cloud-edge Collaboration

Faster and more
efficient



Accelerated Connection

Optimized for speed
and
performance



Localized Data Centers

Ensure data
sovereignty and
compliance in EU &
US



Deye Copilot

AI-powered energy
analysis and control



AI Assistant

24/7 support, fast,
efficient, in your
language



POWERING YOUR LIFE



www.deyeess.com / www.deyeinverter.com



Deye ESS / Deye New Energy