

STACK100

Stack100 is suitable for residential and small commercial and industrial scenarios. Rackless and stackable design is easy to plug and play. It supports 12 clusters in parallel with a maximum capacity of 921kWh and supports 1C charge/discharge.



Flexible Expansion

Up to 12 units in parallel,
15KWh—921KWh capacity



Ultra Safe

Intelligent fire extinguishing
system, react within 5 seconds



1C Rate

Suitable for grid frequency regulation,
charging stations and other scenarios,
cost saving



Easy Installation

0 wiring, rackless free stacking,
plug-and-play, one cluster installation in
30min



Long-term Reliability

LFP cells, 0 decay in 3 years, 10
years long warranty



Module Mixing

Free mixing of modules
within three years

Specification

Model	STACK100
Battery Type	LiFePO4
Module Voltage/Capacity	51.2V/100Ah
Single Module Weight	47Kg
System Modules Serial Number	3~15
System Energy Range	15.36~76.8kWh
Operating Voltage	134~864V
Recommended Charge/Discharge Current	50A (0.5C)
Max.Charge/Discharge Current	100A (1C)
Peak Discharge Current(2min 25°C)	125A(1.25C)
Depth of Discharge	95%
Communication	CAN/RS485
Cycle Life *	Unlimited cycles / 10 Years
Max. Single Cluster Dimension[W*D*H](mm)	591 / 390 / 1700~11 module
Charging Temp. Range	0~55°C
Discharging Temp. Range	-20~55°C
Protection Level	IP20
Fire Protection System	Aerosol fire extinguisher
Installation method	Stack type
Cooling method	Forced wind cooling
WiFi Module	Built-in WiFi module; APP OTA function
Certification & Safety Standard	CE-EMC/CE-RED/62619/63056/62477/62040/UN38.3
Compatible Inverters	Ingeteam/Solis/GoodWe/Growatt/Solplanet/SAJ/DEYE/Hoymiles/SOLINTEG ect.

* Test conditions: 0.2C Charging & Discharging. @25°C, 95% DOD

